

ALPHA BRIDGE LAYER 2 Unmanaged Switches (AS200/16/T/U)











Carrier-Grade, High

Routing Functions.

Verified Service characteristics, Versatile IPv6 solution, Complete Security Mechanism.



Supports Max. 16 GE TX Ports.

Product Characteristics

Switching Characteristics

- Non-block switching architecture and wire-speed forwarding supported by all ports.
- Large-buffer and HD video.
- IEEE802.3x full duplex flow control and Backpressure halfduplex flow control.
- Multi-functional DIP (dial-up switch), satisfying the requirement of different networks.

Practicability

- Plug and play; no need of configuration;
- Its LED indicates working status and error information

Reliability

- Integrated professional thunder-proof electric circuit, adaptable to the outdoor environment.
- Complies with CE, FCC.
- Contact and small, fit for water-proof cabinet in the outdoor monitoring scenarios and buildings
- 0-50°C working temperature.

Product Overview

Alpha Bridge AS200/16/T/U is a high cost-effective unmanaged switch designed by Alpha Bridge for the network in medium and small offices.

Alpha Bridge AS200/16/T/U satisfies the requirement of networks in different scales such as hotels, campuses, dormitories and other medium and small enterprises.

Model



AS200/16/T/U

16 GE TX



Product Specifications

AS200/16/T/U
32G
8K
16 GE TX
4M
Standard, flow control, isolated
24 Mpps
Storage-and-forward
Built-in AC
Fan Iess, Noise-Free Cooling
280x125x44
220×150×40
Built-in AC: 100~220V, 50Hz±10%

Ordering Information

Item	Description
AS200/16/T/U	Ethernet unmanaged switch with 16 gigabit TX ports (16 gigabit TX ports, 4 DIP groups, large buffer, thunder-proof, AC220V, fan less, 11-inch chassis, rack-mounted installation)