

ALPHA BRIDGE LAYER3-Lite Switch (AS200/54XT)



Supports Max. 48 GE TX Ports and 6 10G SFP+ Uplink Ports.



Advanced Hardware Architecture and Industry-leading Port Density.



Carrier-Grade, High Reliability, Layer-3 Routing Functions.



Verified Service characteristics, Versatile IPv6 solution, Complete Security Mechanism.

Product Overview

AS200/54XT is the next-generation aggregation 10GE switch portfolio introduced by ABTPL. It targets the IP MAN (Metropolitan Area Network), Government and Enterprise Networks, Internet cafe, and Disk-Less working environments. It is developed based on high-performance hardware and ABOS software platform with ABTPL's own independent intellectual property rights. It supports functions such as powerful ACL, flexible Q-in-Q, 1:1 or N:1 VLAN switching, Ethernet OAM, carrier-level QoS, and industry-level 10GE Ether-ring, ensuring this switch series meets application requirements in all kinds of complicated sites. It also supports layer-3 routing protocol.

Product Characteristics

Virtual Cluster Switching

Alpha Bridge Series virtualizes multiple physical devices into one. The performance, reliability and management of the virtual system are superior to the physical ones.

High Reliability: Based on the advanced distribution mechanism and efficient cross-physical link aggregation link functions, the logical control plane, service control plane and service data plane are separated.

Alpha Bridge Series supports In-Service Software Upgrade (ISSU) to ensure the uninterrupted data forwarding during system upgrade.

It can support continuous layer-3 routing forwarding, avoiding service interruption as a result of a single point of failure. **Easy Management:** the OS realizes single IP management, greatly improving the networking efficiency and lowering the operating cost.

Product Characteristics

Telecom-Level Ethernet Switch

Supports the telecom-level Ethernet-ring protection protocol with a protection shift time of less than 50ms, STP/RSTP/MSTP, backup of active/standby uplinks and LACP link aggregation to cater to the requirements of high reliability of carriers.

Supports Ethernet standards 802.3u, 802.3x, 802.3ad, 802.1d, 802.1p, 802.1q, 802.1w, 802.1ad.

Supports system status LED, port dynamic LED. Provides the perfect Ethernet OAM mechanism to monitor the network running status in real-time for rapid trouble locating and detection. Supports powerful ACL functions to access and control L2-L7 data based on physical port, VLAN, MAC, IP and protocol port ID and providing flexible and various policy control methods to carriers. Supports In-Service Software Upgrade (ISSU) to ensure the uninterrupted data forwarding during system upgrade. fast-leave and trans-vlan.

Flexible & Convenient Management and Maintenance

Supports management modes such as the console port, Telnet, SSH, etc.

Supports WEB management mode, which is easy and efficient so that it makes installation and debugging convenient.

Supports TFTP-patterned file upload/download management.

Supports ISSU (In-Service Software Upgrade).

Supports SNMP and ABTPL NMS smart network management platform to realize automatic equipment discovery, network topology management, equipment configuration management, performance data statistics and analysis and trouble management.

Perfect Security Mechanisms

Equipment-level security: The advanced hardware infrastructure design ensures packet protection, prevents DoS-/TCP-related SYN Flood, UDP Flood, Broadcast Storm or large traffic attacks, and supports level-based command line protection, endowing different levels of users with different management permissions. Perfect security authentication mechanisms: IEEE 802.1x, Radius and Open source TACACS+.

AS200/54XT series supports storm/multicast/unicast limit, ensuring the normal running of equipment in harsh network conditions.

AS200/54XT series supports perfect ring detection mechanism, ensuring the long-term stable running of network. Supports port isolation within the same VLAN, DHCP-Snooping, and IP plus MAC plus Port binding for ensuring user data security.

Industrial Ethernet Ring with “0” Delay/Packet Loss

Supports industry-level EAPS with protection shift time less than 50ms. Their high reliability is represented by the null packet loss, which has been proved by multiple test scenarios.

Versatile IPv6 Solutions

Supports the IPv6 protocol suite, IPv6 neighbor discovery, ICMPv6, path MTU discovery, etc.

Supports Ping, Traceroute, Telnet, SSH, ACL and so like based on IPv6, meeting IPv6 network equipment management requirements and service control requirements.

Carrier-Level QoS Policies

Alpha Bridge AS200/54XT series supports priority retagging and complicated flow classification based on VLAN, MAC, source address, destination address, IP or priority, eventually streamlining carrier’s services in a better way.

Alpha Bridge series provides flexible bandwidth control policies, supporting port/flow-based Low limit, ensuring the line speed forwarding of each port.

AS200/54XT Series supports multiple queue schedule algorithms such as SP, WRR and “SP + WRR”.



Product Specifications

| Item | AS200/54XT |
|---|-------------------------|
| Interface | 48 GE TX 6 10GE/GE SFP+ |
| Console (RJ45) | 1 |
| Backplane (Gbps) | 216 |
| Forwarding rate (Mpps with 64 bytes) | 162 |
| Chassis Dimensions (WxDxH) (mm) | 440x280x44 |
| Chassis Weight (KG) (empty) | 4.3 |
| Package Dimensions (WxDxH) (mm) | 576x448x94 |
| Package Dimensions Weight (KG) | 5.5 |
| Power consumption (No-load) | < 25W |
| Power consumption (Full-load) | <48W |
| Power supply AC: 100-240V / DC: 36-72V | 50W |
| PE power budget | NA |
| Total output BTU (1000 BTU/H = 293W) | 163.82 |
| Fan number | 2 |
| Noise@25°C (dBA) | 45 |
| MTBF(H) | > 200,000 |
| Forwarding mode | Store-forward |
| Flash (MB) | 16 |
| DRAM (MB) | 512 |
| MAC | 16K |
| Buffer size (MB) | 1.5 |
| Interface VLAN | 64 |
| Routing table | 512 |
| Jumbo frame | 9K |

Product Features

| VLAN | QoS | Reliability |
|--|--|--|
| 4K Active VLAN, Q-in-Q & Selective Q-in-Q, GVRP, Private VLAN, Voice VLAN | CAR, HQoS, MAC/IP/TCP/UDP/VLAN/ COS/DSCP/TOS based QoS, 802.1P/ DSCP priority re-labeling, SP, WRR, and "SP+WRR", Tail-Drop, WRED, flow monitoring and traffic shaping | Static/LACP link Aggregation, Interface backup, EAPS and ERPS, ISSU uninterrupted system upgrade, VSS, ups to 16-units per stack, VRRP, UDLD |
| Spanning Tree | Security | Accessories |
| 802.1D (STP), 802.1W (RSTP) and 802.1S (32 instances MSTP) BPDU guard , root guard and Loopback guard | Port isolation, Port security, IP+MAC+port binding, MAC sticky, IEEE 802.1x, Radius and Tacacs+, MD5, SHA-256, RSA-1024, AES256, L2/L3/L4 ACL flow identification and filtration, Anti-attack from DDoS, TCP's SYN Flood, UDP Flood. | Power cord, rackmount kits, console cable |
| | | Certification |

| | | |
|---|---|--|
| | Broadcast/Multicast/unknown unicast storm-control. DAI & IP source guard, PPPoE+ | CE, ROHS |
| IP | DHCP | Multicast |
| Static route, RIP, OSPF IP v4/V6 Dual stack, DHCP server /Client Relay. | DHCP server/relay/client, DHCP snooping/option82 | IGMP v1/v2/v3, IGMP Snooping, IGMP Fast Leave, MVR, IGMP filter |
| IPv6 | Environment | Management |
| ICMPv6, DHCPv6, ACLv6 and IPv6 Telnet, IPv6 neighbor discovery, Path MTU discovery, MLD V1, MLD snooping, IPv6 Static Routing, RIPng, OSPFv3, Manual tunnel, ISATAP tunnel, 6 to 4 tunnel | Operating temperature/humidity: 0°C to 50°C, 10%-90% Non-condensing Storage temperature/humidity: (-20°C to 70°C), 5%-95% Non-condensing | Console, Telnet, SSH v1/2, HTTP, HTTPS, SNMP v1/v2/v3, RMON, TFTP, FTP, SFTP, Dying gasp*, NTP, ZTP(Zero Touch Provisioning),SYSLOG, SPAN, RSPAN |

Model

AS200/54XT

48 GE TX
6 10GE/GE SFP+



Ordering Information

| Item | Description |
|------------|---|
| AS200/54XT | Ethernet Layer-3 lite switch with 48 GE and 6 10GE/GE SFP+ ports (1 Console port, 48 GE TX ports, 6 10GE/GE SFP+ ports; 100 to 240 VAC input, 60 HZ, the cooling fan, 1U, standard 19-inch rack-mounted installation) |