

ALPHA BRIDGE

LAYER 2 Unmanaged Switches (AS200/8T-U)



Supports Max. 8 GE TX Ports.



Fan less, Noise-Free Cooling, Multi-functional DIP



High Reliability, Built-in AC: 100~220V, 50Hz±10%.



Verified Service characteristics, Complete Security Mechanism.

Product Overview

Alpha Bridge AS200/8T-U is a high cost-effective unmanaged switch designed by Alpha Bridge for the network in medium and small offices.

Alpha Bridge AS200/8T-U has eight models involving three series, 100M, gigabit uplink and full-gigabit, which satisfies the requirement of networks in different scales such as hotels, campuses, dormitories, and other medium and small enterprises.

Model info

AS200/8T-U
8 GE TX



Product Characteristics

Switching Characteristics

- Non-block switching architecture and wire-speed forwarding supported by all ports.
- Large-buffer and HD video.
- IEEE802.3x full duplex flow control and Backpressure half-duplex flow control.
- Multi-functional DIP (dial-up switch), satisfying the requirement of different networks.

Practicability

- Plug and play; no need of configuration;
- Its LED indicates working status and error information

Reliability

- Integrated professional thunder-proof electric circuit, adaptable to the outdoor environment.
- Complies with CE, FCC.
- Contact and small, fit for water-proof cabinet in the outdoor monitoring scenarios and buildings
- 0-50°C working temperature.

Product Specifications

Item	AS200/8T-U
Switching Capacity	16G
MAC	4K
Service Ports	8 GE TX
Uplink Port	-
Port cache	2M
Functional DIP	standard, isolated, extended
Forwarding rate (Mpps)	12 Mpps
Forwarding mode	Storage-and-forward
Power supply	Power adapter
Heat dissipation	Fan less, Noise-Free Cooling
Package Dimensions (WxDxH) (mm)	137x77x25
Chassis Dimensions (WxDxH) (mm)	140x78x28
Power supply	Built-in AC: 100~220V, 50Hz±10%

Ordering Information

Item	Description
AS200/8T-U	Ethernet unmanaged switch with 8 gigabit TX ports (8 gigabit TX ports, 3 DIP groups, loop alarm LED indicator, external power adapter, 5V/1A (5~12V DC input), fanless, desk-top installation)

Copyright @ Alpha Bridge Technologies Private Limited

This document is ABTPL Public Information. ABTPL reserves the right to alter, update and otherwise change the information contained in the document from time to time.
www.alphabridge.tech