

ALPHA BRIDGE XGPON ONT AN6000/2/4/V/U-X



Verified Service characteristics, Versatile IPv6 solution, Complete Security Mechanism.



Advanced Hardware Architecture and Industry-leading Port Density.

XGPON

10 Gigabit Passive optical networks have been a staple for service providers worldwide but have primarily focused on fibre to the home and metro Ethernet residential deployments. A number of different deployment scenarios have emerged that effectively leverage many of the strengths of the PON topology.

• Hospitality/healthcare

- Deliver end users predictable and stable connectivity.
- Offer data, voice, and video with the same infrastructure.
- Point-to-multipoint distribution network for scale.
- Simple and stable deployment in spread-out areas.

• Public sector

- Offer critical service and security dependencies to make sure the services are performing without any attack - Offer data, voice, and video with the same infrastructure.
- Simple and stable deployment in spread-out areas.

• Commercial buildings

- Highly available network infrastructure with energy efficiency and space savings.
- Cope with constantly changing environments without rewiring or additional investment.

Product Overview


ABTPL's AN6000/2/4/V/U-X is a XGPON optical terminal access device (AX3000Mbps) that is highly integrated with dual-frequency Wi-Fi6. It is the end-product of optical fiber for operators. It supports ultra-bandwidth access through XGPON upstream technology and provides users with basic WIFI functions, routing, and gigabit Ethernet functions. The upstream network ports of the AN6000/2/4/V/U-X are XGPON ports. The downstream user ports include four GE electrical ports, one USB port, one VOIP port and WiFi6 WLAN ports.

Interface function

- 1 * XGPON interface: SC/UPC/APC interface, XGPON standard
- 1*2.5G+3*GE Ethernet interface: 10/ 100/ 1000 Mbps, RJ - 45, IEEE802.3-2005 standard
- 1 * VOIP interface: in accordance with G. 711 a/u, G. 729 a/b, G. 722 standard
- 1 * USB interface: standard USB 3.0 interface
- Dual-band WiFi6(2*2 MIMO (2.4G & 5G))

Product Specifications

Hardware Parameters		Wifi 6	
LED	POWER+PON/LOS+NET+LAN +POTS+WiFi+WPS+USB	WiFi protocol	2.4GHz supports 802.11b/g/n 5GHz supports 802.11a/n/ac/ax
Port	1*2.5G+3*GE	Transmit power	2.4G 100mW, 5G/200mW
	1*RJ11 (POTS)	Antenna gain	5dBi
	1*Reset+1*Power +1*LED button+1*WiFi Button +1*WPS	Antenna	dual-antenna MIMO (2*2) (2.4G & 5G)
	1*SC/UPC (or SC/APC)	WLAN penetrate	One reinforced concrete wall or two ordinary brick walls (non-reinforced concrete)
	1*POTS	WLAN access capability	64/SSID
	1*DC	channel	2.4GHz (channel 1-13) 5GHz (channel 36-161)
	1*USB 3.0	WPS	WLAN terminal devices with WPS Push Button function establish connection within 2 minutes
Size	190mm*135mm*33mm(L*W*H)	WLAN security function	WPA-PSK, WPA2-PSK, WPA3, WPA- PSK/WPA2-PSK AES, AES+TKIP
Consumption	≤ 10W	Air Speed	574 Mbps (2.4GHz), 2402
Flash	256MB NAND		
Memory	512MB DDR4		
Interface Parameters			
Ethernet Port	Ethernet port-based VLAN tags and tag removal, VLAN transparent and mark, MAC address learning, 10/100/1000Mbps Auto negotiation		
XGPON Port	Class B + optical system Maximum Receive Sensitivity: -8 dBm Minimum reception sensitivity: -28 dBm Wavelengths: US 1270 nm, DS 1577nm 10G downstream/2.5G upstream		
USB	USB3.0		
VoIP Port	Call waiting, Unconditional Call Forward, Call Forward if Busy, Call Forward if no reply and Three-party calls. G711A/G711U/G729/G722 SDP protocol (RFC 2327 and RFC 4566) T.30/T.38/G.711 fax mode, DTMF		



Product Features

XGPON	QoS	Layer 2 Features
ITU-T G.987.3, G.988, G.989, 15 TCONTs /256GEM ports, 8 Egress queues per TCONT at least, VLAN/priority/VEIP gem mapping mode, SN/LOID/SN+ Password, authentication Performance, monitoring: eth/Gem port Dying gasp	Support 8 Queues with Strict Priority, Ethernet port rate limitation, 802.1p priority, SP/WRR, Service flow classification	MAC learning (SVL)/aging Support max frame length to 1518 bytes VLAN tagging for untagged packets Support VLAN 1-4094 VLAN transparent/translation
Layer 3 Features	Multicast	Management
PPPoE/Static IP/DHCP, NAT/NAPT, Port forwarding ALG, UPnP, DDNS, IPv6/IPv4 dual stack, and DS-Lite Static/Default routes, Multiple services on one WAN port, RIPv2 with passive mode	IGMP v2 (RFC 2236) and IGMP v3 (RFC 3376) IGMP snooping and IGMP, Proxy MLD v1/v2	OMCI/Web UI/TR069, Telnet/SSH management with CLI commands Dual-system software backup and rollback
		Environment
		Storage Temperature: -20 °C - 70 °C Operating Temperature: 0 °C - 45 °C Operating Humidity: 5%-95% (non-Condensing) Power Supply: 12V/1.5A

Ordering Information

Item	Description
AN6000/2/4/V/U-X	1*2.5G+3*GE RJ45 Ports, 1 RJ11 Port, 1*Reset+1*Power +1*LED button+1*WiFi button+1*WPS, 1*SC/UPC (or SC/APC), 1*USB 3.0, 1*DC, DC Power Supply: 12V/1.5A

Copyright @ Alpha Bridge Technologies Private Limited

This document is ABTPL Public Information. ABTPL reserves the right to alter, update and otherwise change the information contained in the document from time to time.
www.alphabridge.tech