

# ALPHA BRIDGE

## LAYER 2 Unmanaged Switches (AS200/26T-U)



Supports Max. 24 TX +  
1 GE TX, 1GE SFP  
Uplink Ports.



Advanced Hardware  
Architecture and Industry-  
leading Port Density.



Carrier-Grade, High  
Reliability, Layer-3  
Routing Functions.



Verified Service  
characteristics, Versatile  
IPv6 solution, Complete  
Security Mechanism.

### Product Overview

Alpha Bridge AS200/26T-U is a high cost-effective unmanaged switch designed by Alpha Bridge for the network in medium and small offices.

Alpha Bridge AS200/26T-U which satisfies the requirement of networks in different scales such as hotels, campuses, dormitories and other medium and small enterprises.

### Model

**AS200/26T-U**  
24 TX + 1GE TX  
1GE SFP



### Product Characteristics

#### Switching Characteristics

- Non-block switching architecture and wire-speed forwarding supported by all ports.
- Large-buffer and HD video.
- IEEE802.3x full duplex flow control and Backpressure half-duplex flow control.
- Multi-functional DIP (dial-up switch), satisfying the requirement of different networks.

#### Practicability

- Plug and play; no need of configuration;
- Its LED indicates working status and error information

#### Reliability

- Integrated professional thunder-proof electric circuit, adaptable to the outdoor environment.
- Complies with CE, FCC.
- Contact and small, fit for water-proof cabinet in the outdoor monitoring scenarios and buildings
- 0-50°C working temperature.

## Product Specifications

Item	AS200/26T-U
Switching Capacity	56G
MAC	8K
Service Ports	24 TX ports
Uplink Port	2 GE SFP Ports
Port cache	4M
Functional DIP	Standard, isolated, extended
Forwarding rate (Mpps)	39 Mpps
Forwarding mode	Storage-and-forward
Power supply	Built-in AC
Heat dissipation	Fan less, Noise-Free Cooling
Package Dimensions (WxDxH) (mm)	440x205x44
Chassis Dimensions (WxDxH) (mm)	440x208x44
Power supply	Built-in AC: 100~220V, 50Hz±10%

## Ordering Information

Item	Description
AS200/26T-U	Ethernet unmanaged switch with 24 gigabit TX ports and 2 gigabit SFP ports (24 gigabit TX ports, 2 gigabit SFP ports, 3 DIP groups, large-buffer, thunder-proof, AC220V, fan less, 19-inch chassis, rack-mounted installation).

### Copyright @ Alpha Bridge Technologies Private Limited

This document is ABTPL Public Information. ABTPL reserves the right to alter, update and otherwise change the information contained in the document from time to time.  
[www.alphabridge.tech](http://www.alphabridge.tech)