


Alpha Bridge
AB-QSFP 28-03
Datasheet



Features

- Supports 103.1Gb/s aggregate bit rate
- 4x25Gb/s electrical interface
- Maximum link length of 300m on OM4 Multimode Fiber (MMF)
- Hot-pluggable QSFP28 footprint
- Single MPO 12 receptacle
- Low power Consumption
- RoHS-6 compliant and lead-free
- +3.3V single power supply
- Support Digital Diagnostic Monitor interface
- Case operating temperature Commercial: 0°C to +70°C

Applications

- 100GBASE-SR4 100G Ethernet

Compliance

- QSFP28 MSA.
- IEEE802.3bm
- SFF-8636
- RoHS

Absolute Maximum Ratings

| Parameter | Symbol | Min. | Typ. | Max. | Unit | Ref. |
|---------------------------------|--------|------|------|--------|--------|------|
| Storage Temperature | TS | -40 | | 85 | °C | |
| Storage Ambient Humidity | HA | 0 | | 85 | % | |
| Maximum Supply Voltage | VCC | -0.5 | | 3.6 | V | |
| Receiver Damage Threshold | | 3.4 | | | dBm | |
| Lead Soldering Temperature/Time | TSOLD | | | 260/10 | °C/sec | 1 |
| Lead Soldering Temperature/Time | TSOLD | | | 360/10 | °C/sec | 2 |

Note: 1. Suitable for wave soldering.

2. Only for soldering by iron.

General Product Characteristics

| Data Rate Specifications | Symbol | Min. | Typ. | Max. | Unit | Ref. |
|------------------------------------|--------|------|------|--------|--------|------|
| Bit Rate (all wavelength combined) | BR | | | 103.1 | Gb/s | 1 |
| Bit Error Ratio (pre-FEC) | BER | | | 10-May | | 2 |
| Maximum Supported Distances | | | | | | |
| Fiber Type | | | | | | |
| Link distance on OM3 MMF | d | | | 70 | meters | 3 |
| Link distance on OM4 MMF | d | | | 300 | meters | 3 |

Notes:

1. Supports 100GBASE-SR4 per IEEE 802.3bm.
2. Tested with a PRBS 2³¹-1 test pattern.
3. Requires FEC on the host to support maximum distance, per 100GBASE-SR4.

Optical Characteristics

| Parameter | Symbol | Min. | Typ. | Max. | Unit | Ref. |
|--|----------------|-------------------------------|------|-------|------|------|
| Transmitter (per lane) | | | | | | |
| Average Output Power per lane | POUT | -6 | | 2.4 | dBm | |
| Extinction Ratio | ER | 2 | | | dB | |
| Center Wavelength | λ_C | 840 | | 860 | nm | |
| RMS Spectral Width | σ | | | 0.6 | nm | |
| Transmitter OFF Output Power | POff | | | -30 | dBm | |
| Transmitter eye mask definition {X1,X2,X3,Y1,Y2,Y3} | | {0.3,0.38,0.45,0.35,0.41,0.5} | | | | 1 |
| Receiver (per lane) | | | | | | |
| Input Optical Wavelength | λ_{IN} | 840 | | 860 | nm | |
| Rx Sensitivity (OMA) per lane @BER=5E-5 | RSENS | | | -10.3 | dBm | 2 |
| Input Saturation Power (Overload) | PSAT | 2.4 | | | dBm | |
| Receiver Reflectance | Rfl | | | -12 | dBm | |
| Loss of Signal Assert | PA | -30 | | | dBm | |
| Loss of Signal De-assert | PD | | | -12 | dBm | |
| LOS Hysteresis | PD - PA | 0.5 | | | dB | |

Note:

1. Hit Ratio 1.5x10⁻³ hit/sample.
2. Measured with PRBS 2³¹-1 test pattern 25.78125Gbps.

Electrical Interface Characteristics

| Parameter | Symbol | Min. | Typ. | Max. | Unit | Ref. |
|--------------------------------------|-----------------------|------|------|------|----------|------|
| Supply Voltage | VCC1, VCCTX, VCCRX | 3.15 | | 3.45 | V | |
| Supply Current | ICC | | | 750 | mA | |
| Transmitter (per Lane) | | | | | | |
| Input different impedance | Rin | 90 | 100 | 110 | Ω | |
| Single ended input voltage tolerance | VinT | -0.3 | | 4 | V | |
| Single ended data input swing | Vin,pp | 200 | | 1000 | mV | |
| Receiver (per Lane) | | | | | | |
| Output different impedance | Rout | 90 | 100 | 110 | Ω | |
| Single ended data output swing | Vout,pp | 200 | | 1000 | mV | |
| Single-ended output voltage | VoutR | -0.3 | | 4 | V | |

Pin Diagram




Figure 1 – QSFP28-Compliant 38-Pin Connector (Per SFF-8679)


Pin Descriptions

| Pin | Symbol | Name/Description | Ref. |
|-----|---------|-------------------------------------|------|
| 1 | GND | Ground | 1 |
| 2 | Tx2n | Transmitter Inverted Data Input | |
| 3 | Tx2p | Transmitter Non-Inverted Data Input | |
| 4 | GND | Ground | 1 |
| 5 | Tx4n | Transmitter Inverted Data Input | |
| 6 | Tx4p | Transmitter Non-Inverted Data Input | |
| 7 | GND | Ground | 1 |
| 8 | ModSe1L | Module Select | |
| 9 | ResetL | Module Reset | |
| 10 | Vcc Rx | +3.3V Power supply receiver | |
| 11 | SCL | 2-wire serial interface clock | |
| 12 | SDA | 2-wire serial interface data | |
| 13 | GND | Ground | 1 |
| 14 | Rx3p | Receiver Non-Inverted Data Output | |
| 15 | Rx3n | Receiver Inverted Data Output | |
| 16 | GND | Ground | 1 |
| 17 | Rx1p | Receiver Non-Inverted Data Output | |
| 18 | Rx1n | Receiver Inverted Data Output | |
| 19 | GND | Ground | 1 |
| 20 | GND | Ground | 1 |
| 21 | Rx2n | Receiver Inverted Data Output | |
| 22 | Rx2p | Receiver Non-Inverted Data Output | |
| 23 | GND | Ground | 1 |
| 24 | Rx4n | Receiver Inverted Data Output | |
| 25 | Rx4p | Receiver Non-Inverted Data Output | |
| 26 | GND | Ground | 1 |
| 27 | ModPrSL | Module Present | |
| 28 | IntL | Interrupt | |
| 29 | Vcc Tx | +3.3V Power supply transmitter | |
| 30 | Vcc1 | +3.3V Power Supply | |
| 31 | LPMODE | Low Power Mode | |
| 32 | GND | Ground | 1 |
| 33 | Tx3p | Transmitter Non-Inverted Data Input | |
| 34 | Tx3n | Transmitter Inverted Data Input | |
| 35 | GND | Ground | 1 |
| 36 | Tx1p | Transmitter Non-Inverted Data Input | |
| 37 | Tx1n | Transmitter Inverted Data Input | |
| 38 | GND | Ground | 1 |

Note:

1. Circuit ground is internally isolated from chassis ground.


Digital Diagnostic Functions



| | Optional | Optional | Optional | |
|----------------------------|------------------------------------|-------------------------------|-------------------------------------|-----------------------|
| Upper Page 00h | Page 01h | Page 02h | Page 03h | |
| 128 Identifier | 128 CC_APPS | 128-255 User EEPROM Data | 128-175 Free Side Device Thresholds | |
| 129-191 Base ID Fields | 129 AST Table Length (TL) | | | |
| | 130-131 Application code entry 0 | | | |
| | 132-133 Application code entries 1 | | | |
| 192-223 Extended ID | 134-253 other entries | 176-223 Channel Thresholds | | |
| 224-255 Vendor-Specific ID | | | 254-255 Application Code Entry TL | 224 Tx EQ & Rx |
| | | | | Emphasis Magnitude ID |
| | 225 RX output amplitude indicators | | | |
| | | 226-241 Channel Controls | | |
| | | 242-251 Channel Monitor Masks | | |
| | | 252-255 Reserved | | |

Figure 2 – Two-Wire Interface Fields

Mechanical Specifications (Unit: mm)



Unit mm

| | L | L1 | L2 | L3 | L4 | W | W1 | W2 | H | H1 | H2 | H3 | H4 | H5 | H6 |
|------|------|------|-----|------|------|-------|-----|-----|-----|------|------|-----|-----|-----|------|
| Max | 72.2 | - | - | 4.35 | 61.4 | 18.45 | - | 6.2 | 8.6 | 12.4 | 5.35 | 2.5 | 1.6 | 2 | - |
| TYPE | 72 | - | 121 | 4.2 | 61.2 | 18.35 | - | - | 8.5 | 12.2 | 5.2 | 2.3 | 1.5 | 1.8 | 6.55 |
| Min | 68.8 | 16.5 | - | 4.05 | 61 | 18.25 | 2.2 | 5.8 | 8.4 | 12 | 5.05 | 2.1 | 1.3 | 1.6 | - |

Ordering information

| Part Number | Description |
|--------------|---|
| AB-QSFP28-03 | 100G SR4 850nm 300m, MPO-12, 0-70°C, with DDM |

Note: All information contained in this document is subject to change without notice