
Alpha Bridge AB-SFP+-10T Datasheet

Alpha Bridge® Technologies

AB-SFP+-10T
DATASHEET



Features

- Support 9.95Gb/s to 10.3Gb/s data rates
- Simplex LC Connector Bi-Directional SFP+ Optical Transceiver
- Single 3.3V Supply
- Up to 10km on 9/125um SMF
- 1270nm DFB Laser transmitter,1330nm receiver
- Compliant with IEEE 802.3ae 10GBASE-LR and 10GBASE-LW
- SFP+ MSA SFF-8431 Compliant
- Digital Diagnostic SFF-8472 Compliant
- RoHS compliant and Lead-Free
- Operating case temperature: 0°C ~70°C

Applications

- 10GBASE-LR at 10.3125Gbps
- 10GBASE-LW at 9.953Gbps
- Other Optical Links

Description

The SFP+ BWDM series single mode transceiver is small form factor pluggable module for duplex optical datacommunications such as 10GBASE-LR/LW defined by IEEE 802.3ae. It is with the SFP+ 20-pin connector to allow hot plug capability.

The SFP+ BWDM module is designed for single mode fiber and operates at a nominal wavelength of 1270nm; The transmitter section uses a multiple quantum well DFB, which is class 1 laser compliant according to International Safety Standard IEC-60825. The receiver section uses an integrated InGaAs detector (IDP) mountedin an optical header and a limiting post-amplifier IC.

Absolute Maximum Ratings

Parameters	*Symbol*	*Min.*	*Max.*	*Units*
Supply Voltage	*VCC*	-0.5	3.6	V
Storage Temperature	*Tc*	-40	85	°C
Operating Case Temperature	*Tc*	0	70	°C
Relative Humidity	*RH*	0	85	%

Recommended Operating Conditions

Parameter	*Symbol*	*Min.*	*Typ.*	*Max.*	*Units*
Supply Voltage	*VCC*	3	3.3	3.6	V
Supply Current	*Icc*		300	420	mA
Operating Case Temperature	*TC*	0	25	70	°C
Module Power Dissipation	*Pm*		1	1.5	W

Notes:

1. Supply current is shared between VCCTX and VCCRX
2. In-rush is defined as current level above steady state current requirements.

Diagnostics Monitoring

Parameter/Range	*Symbol*	*Accuracy*	*Unit*	*Notes*
Temperature monitor absolute error	*DMI_Temp*	± 3	oC	
Supply voltage monitor absolute error	*DMI_VCC*	±0.3	V	
TX power	*DMI_TX*	± 3 dB	dBm	
RX power	*DMI_RX*	± 3 dB	dBm	
Bias Current monitor	*DMI_Ibias*	± 10%	mA	

Optical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Units	Note
Transmitter						
Optical Wavelength	*λC*	1260	1270	1280	nm	
Side Mode Suppression Ratio	*SMSR*	30			dB	
Spectral Width (-20dB)	*Δλ*			1	nm	
Average Output Power	*Pop*	-2		0.5	dBm	1
Extinction Ratio	*ER*	3.5			dB	
Eye Mask	*Compliant with IEEE 802.3*					
Transmitter Dispersion Penalty	*TDP*			3.2	dB	
Launch Power of OFF Transmitter	P_{OUT_OFF}			-30	dBm	
Relative Intensity Noise	*RIN*			-128	dB/Hz	
Receiver						
Center wavelength	λ_C	1320	1330	1340	nm	
Average Receiver Power	*PSENS*			-14.5	dBm	1,2
Receiver Overload	P_{MAX}			0.5	dBm	
LOS Assert	LOS_A	-30			dBm	
LOS De-assert	LOS_D			-15	dBm	
LOS Hysteresis	LOS_H	0.5			dB	

Notes:

1. Average Receiver Power (Min) is informative and not the principal signal strength indicator. A received power below this value cannot be compliant.
2. Measured with a PRBS2^{31}-1 test pattern @10.3125Gbps, BER≦10-12


Electrical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Units	Note
Supply Voltage	Vcc	3		3.6	V	1
Supply Current	Icc			420	mA	1
Transmitter						
Input Differential Impedance	*Rin*		100		Ω	2
Single-ended data input swing	Vin_{PP}	150		1200	mVpp	
Transmit Disable Voltage	V_D	2		Vcc	V	
Transmit Enable Voltage	V_{EN}	V_{EE}		V_{EE}+0.8	V	3
Receiver						
Output Differential impedance	*Rout*		100		Ω	2
Single-Ended Data Output Swing	V_{OUT_PP}	300		700	mV	4
LOS Fault	$V_{LOS\ fault}$	2		VCC_{HOST}	V	5
LOS Normal	$V_{LOS\ norm}$	V_{EE}		V_{EE}+0.8	V	5

Notes:

1. Module power consumption never exceeds 1W.
2. AC coupled.
3. Or open circuit.
4. Into 100-ohm differential termination.
5. LOS is LVTTL. Logic 0 indicates normal operation; logic1 indicates no signal detected.

Block Diagram of Transceiver




Pin Description

Pin	Name	Description	Notes
1	VEET	Transmitter ground (common with receiver ground)	1
2	TX_FAULT	Transmitter Fault	2
3	TX_DISABLE	Transmitter Disable. Laser output disabled on high or open	3
4	SDA	2-wire Serial Interface Data Line	4
5	SCL	2-wire Serial Interface Clock Line	4
6	MOD_ABS	Module Absent. Grounded within the module	4
		RS0 for Rate Select: Open or Low = Module supports ≤4.25Gbps	
7	RS0	High = Module supports 9.95 Gb/s to 10.3125 Gb/s	
8	LOS	Loss of Signal indication. Logic 0 indicates normal operation	5
9	RS1	No connection required	1
10	VEER	Receiver ground (common with transmitter ground)	1
11	VEER	Receiver ground (common with transmitter ground)	1
12	RD–	Receiver Inverted DATA out. AC coupled	
13	RD+	Receiver Non-inverted DATA out. AC coupled	
14	VEER	Receiver ground (common with transmitter ground)	1
15	VCCR	Receiver power supply	
16	VCCT	Transmitter power supply	
17	VEET	Transmitter ground (common with receiver ground)	1
18	TD+	Transmitter Non-Inverted DATA in. AC coupled	
19	TD–	Transmitter Inverted DATA in. AC coupled	
20	VEET	Transmitter ground (common with receiver ground)	1

Notes:


1. Module circuit ground is isolated from module chassis ground within the module.
2. should be pulled up with 4.7k – 10k ohms on host board to a voltage between 3.15Vand 3.6V.
3. TX Disable is an input contact with a 4.7k~10kΩ pullup to VccT inside the module.
4. Mod_ABS is connected to VeeT or VeeR in the SFP+ module. The host may pull this contact up to Vcc_Host with a resistor in the range 4.7 kΩ to10 kΩ. Mod_ABS is asserted “High” when the SFP+ module is physically absent from a host slot.
5. RS0 and RS1 are module inputs and are pulled low to VeeT with > 30 kΩ resistors in the module.

Dimensions



Optical Receptacle Cleaning Recommendations:

All fiber stubs inside the receptacle portions were cleaned before shipment. In the event of contamination of the optical ports, the recommended cleaning process is the use of forcednitrogen. If contamination is thought to have remained, the optical ports can be cleaned using a NTT international Cletop® stick type and HFE7100 cleaning fluid. Before the mating of patch-cord, the fiber end should be cleaned up by using Cletop® cleaning cassette.



Ordering Information

Model Number	Description
AB-SFP+-10T	10Gbps, Tx1270/Rx1330nm, 10km, LC, DDM, SFP+ 0ºC ~ +70ºC

Note: All information contained in this document is subject to change without notice.

Copyright @ Alpha Bridge Technologies Private Limited
This document is ABTPL Public Information. ABTPL reserves the right to alter, update, and otherwise change the information contained in the document from time to time. www.alphabridge.tech V1.0.20. November.2026